

ENDEAVOR®



Simplified Install & Service with Bluetooth Technology

Built-in Bluetooth® connectivity makes it faster and easier for your contractor to install and service your new system.¹⁰ This can help lower your costs and help make your home comfortable again—fast.

FEATURES AT A GLANCE

Cooling & Heating Efficiencies Up To:
19 SEER2 / 12 EER2 / 8.5 HSPF2

Nominal Sizes: 2 to 5 Tons

Cooling & Heating Capacities:
22.8 to 53 kBTU

EcoNet® Enabled: Yes¹¹

Sound Rating⁶: As low as 58 dB

Compressor Type: Inverter Driven,
Variable Speed³ Twin Rotary


Condenser Coil Type: 7mm


ENERGY STAR®
Certified Cold Climate: Yes¹²

Operating Range:
Cooling: 50–125°F
Heating: -22–70°F

Refrigerant Type: R-410A

PlusOnes:

 **PlusOne® Variable Speed Twin Rotary Compressor & Inverter Drive** – Variable speed operation with EcoNet® Smart Thermostat or legacy and other thermostats.^{3,11}

 **PlusOne Diagnostics¹⁰** – Bluetooth technology aids in quick & easy service

Additional Standard Features:

- Filter Drier (Field-installed)
- Front Seating Service Valves
- Internal Pressure Relief Valve
- Powder Coated Paint
- Rust-resistant Screws
- Optimized Venturi Airflow
- External Gauge Ports
- Easy Accessibility

Limited Warranty²:

Conditional Parts – 10 Years
(registration required—no AHRI-matched system requirement)



Rheem.ca

Nearly 100 Years of Innovation

As the only brand bringing innovative air and water solutions to homes and businesses around the world, Rheem continues to deliver advanced comfort, savings and experiences to our customers—just as we've done for nearly 100 years.



Rheem USA
5600 Old Greenwood Road
Fort Smith, Arkansas 72908



Rheem Canada Ltd. / Ltée
125 Edgeware Road, Unit 1
Brampton, Ontario L6Y 0P5

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

¹Coil only – with TXV, with minimum alterations. ²For complete details of the limited and conditional warranties, including applicable terms and conditions, contact your local Contractor or go to Rheem.com for a copy of the product warranty certificate; warranty applies to a heat pump only or system installation; Does not require the heat pump to be part of a properly matched system as specified by the Manufacturer and the Air Conditioning Heating & Refrigeration Institute (AHRI). ³When installed with the EcoNet Smart Thermostat or with legacy and other thermostats when the utility 1 and 2 jumpers are installed. Features two-stage (70% and 100% capacity) operation when installed with legacy and other thermostats when the utility 1 and 2 jumpers are not installed; The 2-ton model features a single rotary compressor. ⁴Residential Building Electrification in CA: Consumer economics, greenhouse gases and grid impacts, April 2019. ⁵Rheem's goal is to release by 2025 a line of heating, cooling, and water heating products that reduce greenhouse gas emissions by 50% as compared to products available in 2019. Reduction calculations will be based on the products' use phase emissions only and utilize average emission factors to account for variability in electricity grids. Reduction calculations will not consider upstream or manufacturing impacts, but use phase emissions account for the majority of the products' impact. At this time, these figures have not been independently verified by a third party. ⁶Based on Internal R&D Testing, 2023. Sound levels are also dependent on proper installation and location of outdoor product. ⁷When installed as part of a complete AHRI-matched Rheem EcoNet-enabled system; Does not apply to coil-only matched systems. ⁸Valid for qualifying AHRI-matched Rheem systems; Proper sizing and installation of equipment is critical to achieve optimal performance. Ask your contractor for details or visit EnergyStar.gov. ⁹WiFi broadband internet connection required. Download the EcoNet® App from the App Store® or Google Play® to set up your EcoNet Smart Thermostat. Receipt of notifications depend on home WiFi setup. Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates. ¹⁰When installed as part of a complete Rheem system where both the outdoor and indoor components feature Bluetooth Technology. ¹¹When installed as part of a complete AHRI-matched Rheem EcoNet-enabled system. ¹²70% heating capacity at 5°F on all tonnages when part of a qualifying AHRI-matched Rheem EcoNet enabled system.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Rheem® is under license. Other trademarks and trade names are those of their respective owners.



© 2024 Rheem Manufacturing Company. Rheem trademarks owned by Rheem Manufacturing Company.

Printed in the USA | 02/24 | QG | Form No. M11-3126 | Rev. 0

TIGHT SPACES. QUIET PLACES.

ENDLESS POSSIBILITIES.

 Side-Discharge
Universal
Heat Pump
RD17AZ



ENDEAVOR®

Rheem® Endeavor® Line Classic Plus® Series

Compatible with nearly any existing HVAC system—or as a universal replacement¹—the EcoNet® enabled Rheem Endeavor Line Classic Plus Series RD17AZ Universal Heat Pump excels in all install situations. And as part of our Sound & Space Constraint Solution, it features a compact footprint, making it the perfect solution when space is at a premium.

Rheem.ca/Endeavor



HEATING  COOLING  WATER HEATING 

Comfort & Efficiency Made Universal

Innovation You Can Count On

Patented industry-first features and 360+1 design make the Rheem Endeavor RD17AZ a smart choice.



Peace-Of-Mind Performance

Relax, you're covered by one of the best warranties in the industry²— 10 Year Conditional Parts when installed as a heat pump only or as part of a system.



Energy Savings

Just like a vehicle's MPG rating, the higher the SEER2, EER2 and HSPF2 rating (Seasonal Energy Efficiency Ratio / Energy Efficiency Ratio / Heating Seasonal Performance Factor), the higher the efficiency of your heat pump—resulting in more energy savings. Keep in mind, other factors such as system matching, sizing, ductwork and installation also impact the overall efficiency. By working with a properly trained contractor, you can be confident that you are choosing the best heating and cooling system for your home's comfort—and your finances.



Precise Comfort

Inverter driven, variable speed, twin rotary compressor technology features fully variable cooling and heating operation between 45% and 100% of capacity³ to continuously meet your ever-changing needs. You'll enjoy exact temperature and advanced humidity control that combine to exceed your optimal comfort expectations.



Space-Saver Solution

Part of our Sound & Space Constraint Solution, the *Classic Plus* Side-Discharge Universal Heat Pump is the ideal product for when installation locations are cramped. It features a small footprint with size options as low as 40.2" wide, 16.4" deep and 36.6" tall. This unit was designed to deliver whole-home comfort quietly and efficiently—further proof that good (and quiet) things come in small packages.



Reduced Emissions

Households generate 72%⁴ of greenhouse gas emissions, so switching to a heat pump can make a big difference for the environment—today.



Durable Curb Appeal

Steel panels provide excellent support and protection to internal components, while the overall modern cabinet aesthetics including the powder coat paint system and rust-resistant screws allow your unit to put its best face forward for years to come.



Less Environmental Impact

The 7mm condenser coil reduces refrigerant requirements up to 15%. This lowers the amount of greenhouse gases emitted while contributing to Rheem's sustainability goal of a 50% reduction in our greenhouse gas footprint by 2025.⁵ A win for all of us.



Universal Install Compatibility


The RD17AZ works with nearly any HVAC system option—including Rheem EcoNet enabled and non-communicating systems, or as a universal replacement with minimal alterations required.¹ Whether your choice is driven by space or sound constraints, electrification initiatives or dual fuel opportunities—this is the comfort solution for you.



Quiet Operation

Efficient home comfort shouldn't be noisy. That's why our heat pumps are designed with acoustics in mind. Sound-dampening features such as refrigerant tubing design, fan blade approach and innovative compressor and drive technologies ensure that as efficiency goes up, sound levels stay low—as low as 58 dB.⁶

SOUND RATING



Helping You Live Both Comfortably & Sustainably

Many Rheem products have sustainability features, but the RD17AZ has earned our Sustainability Standout[®] seal⁷, indicating it's among the best of the best. We created the seal to help you more easily find the products that save energy, save money and save the planet.



Among Heat Pumps, This One's A Star⁸

Earning ENERGY STAR[®] recognition means products meet strict energy efficiency guidelines set by Natural Resources Canada. ENERGY STAR certified heating and cooling equipment can enhance the comfort of your home while saving energy—which saves money on utility bills and protects our climate by reducing harmful carbon pollution and other greenhouse gases.



ENDEAVOR[®]

AVAILABLE MODELS	
Model No.	Description
RD17AZ24AJ3NA	2 ton
RD17AZ36AJ3NA	3 ton
RD17AZ48AJ3NA	4 ton
RD17AZ60AJ3NA	5 ton



The Rheem Endeavor RD17AZ—when installed as part of a complete AHRI-matched, Rheem EcoNet-enabled system—operates with the easy-to-use EcoNet Smart Thermostat, which optimizes system performance and provides a new level of protection and precision comfort **with features like:**

- Communication with latest sensor technology
- Control of your thermostat from anywhere via the EcoNet App⁹
- Alerts sent directly to your phone or email



EcoNet Mobile App



EcoNet Smart Thermostat



ENDEAVOR[®]



To learn more visit Rheem.ca/Endeavor

General Data



GENERAL DATA				
Model No.	RD17AZ24AJ3NA	RD17AZ36AJ3NA	RD17AZ48AJ3NA	RD17AZ60AJ3NA
Nominal Tonnage	2	3	4	5
Valve Connections				
Liquid Line O.D. – in.	3/8	3/8	3/8	3/8
Suction Line O.D. – in.	3/4	3/4	7/8	7/8
Refrigerant (R410A) Furnished oz.	81	116	222	236
Compressor Type	7mm	7mm	7mm	7mm
Outdoor Coil				
Net Face Area – Outer Coil – sq. ft.	11.0	15.1	17.2	17.2
Net Face Area – Inner Coil – sq. ft.	N/A	15.1	17.2	17.2
Tube Diameter – in.	0.276	0.276	0.276	0.276
Number of Rows	1	2	3	3
Fins Per Inch	18	18	16	16
Outdoor Fan				
Diameter – in.	26	28	24	24
Number of Blades	3	3	3	3
Motor HP	1/2	1/2	1/3	1/3
Number of Fans	1	1	2	2
CFM	3,175	3,575	5,150	5,600
RPM	550	570	650	700
Watts	115	215	315	365
Shipping Weight – lbs.	205	271	354	356
Operating Weight – lbs.	146	200	278	280

Earning ENERGY STAR® Cold Climate Certification



Every tonnage of the RD17AZ has earned ENERGY STAR® Cold Climate certification, when installed as part of an AHRI-matched EcoNet-enabled system. To earn the designation, heat pumps must meet or exceed a series of criteria designated by the Department of Energy for cold climate operation.



ENDEAVOR



To learn more visit
Rheem.ca/Endeavor

Unit Dimensions & Available Accessories

UNIT DIMENSIONS						
Model No.	OPERATING			SHIPPING		
	Height in. (mm)	Length in. (mm)	Width in. (mm)	Height in. (mm)	Length in. (mm)	Width in. (mm)
RD17AZ24AJ3NA	36.61 (930)	40.16 (1,020)	16.38 (416)	43.31 (1,100)	48.43 (1,230)	22.05 (560)
RD17AZ36AJ3NA	46.38 (1,178)	42.01 (1,067)	19.29 (490)	53.94 (1,370)	50 (1,270)	25 (635)
RD17AZ48AJ3NA	57.8 (1,468)	40.16 (1,020)	16.38 (416)	65.16 (1,655)	48.43 (1,230)	22.05 (560)
RD17AZ60AJ3NA	57.8 (1,468)	40.16 (1,020)	16.38 (416)	65.16 (1,655)	48.43 (1,230)	22.05 (560)



2 ton
RD17AZ24AJ3NA

3 ton
RD17AZ36AJ3NA

4 ton
RD17AZ48AJ3NA

5 ton
RD17AZ60AJ3NA

ACCESSORIES					
Model No.	RD17AZ24AJ3NA	RD17AZ36AJ3NA	RD17AZ48AJ3NA	RD17AZ60AJ3NA	
Compressor Crankcase Heater	44-103663-15	44-103663-15	44-103663-15	44-103663-15	
Basepan Heater	44-109957-01	44-109958-01	44-109957-01	44-109957-01	
Low Ambient Control	Included	Included	Included	Included	
Compressor Sound Cover	Included	Included	Included	Included	
Low Pressure Control	Included	Included	Included	Included	
High Pressure Control	Included	Included	Included	Included	
Liquid Line Solenoid (24 VAC, 50/60 Hz)	Valve	200RD2T3TVLC	200RD2T3TVLC	200RD2T3TVLC	200RD2T3TVLC
	Coil	61-AMG24V	61-AMG24V	61-AMG24V	61-AMG24V
Liquid Line Solenoid (120/240 VAC, 50/60 Hz)	Valve	200RD2T3TVLC	200RD2T3TVLC	200RD2T3TVLC	200RD2T3TVLC
	Coil	61-AMG120/240V	61-AMG120/240V	61-AMG120/240V	61-AMG120/240V

We Thought of Everything... & Then Some



We evaluate every detail of a product from top to bottom, inside and out and every angle in between. That's 360+1. And that's why you can count on this heat pump to bring you and your family years of efficient and dependable comfort.



TESTED. TRUSTED. TOUGH.

From the smallest part to complete comfort systems, we build quality into everything we make to be sure it's tough enough to deliver the ultimate performance you count on day after day, year after year. That reliability is what makes Rheem different—and better.

ENDEAVOR



To learn more visit
Rheem.ca/Endeavor